

同步变速轮胎压路机  
Pneumatic Tire Rollers

CHANGLIN  
中国工程机械十大专业品牌



本系列是光面轮胎压路机，主要适合于路面工程中各种粘性和非粘性材料，如沙土，碎石，稳定土、沥青混凝土，干硬性混凝土等材料的压实，尤其适宜于高等级公路的沥青面层的最终处理，是建设高等级公路、机场、市政工程及工业场地的高性能压实设备。

Pneumatic smooth-tire rollers is suitable for compaction of various cohesive and non-cohesive materials such as sandy soil, crushed stone, stabilized soils, bituminous concrete and rolling cement concrete (RCC) on road surface construction, especially for final compaction of asphalt surface on high-class highway, which is super quality compaction equipments for high-class highway, airport, municipal road and industrial ground.

主要特点

- 著名品牌水冷增压型发动机，动力强劲，性能先进；
- 内设换挡同步器变速箱，性能先进，操作方便；
- 动力洒水系统完全采用防锈材料，大容量玻璃钢水箱，延长作业时间；
- 具有红外线夜视功能作业监视系统，操作作业极为便利；
- 整机结构紧凑，低重心设计，造型美观；
- 宽敞封闭驾驶室，设有通风设施和空调装置（选择配置），操作舒适。
- Famous brand of diesel turbocharged and water-cooled engines with advanced performance.
- Compact gearbox with speed-shift synchronous unit gearbox for advanced design and convenient control.
- Power sprinkler system with corrosion free materials and 800L high capacity reinforced polyethylene water tank for extended operation.
- Infrared vehicle video monitor system for convenient operations.
- Unique beautiful and compact appearance with lower gravity-center.
- Spacious and closed operator's cab with ventilating and air conditioning devices (optional).

主要技术参数

| 型号        |                                 |        | 8302L             | 8262L              | 8162L              |
|-----------|---------------------------------|--------|-------------------|--------------------|--------------------|
| 最大工作质量    | Max. operating mass             | kg     | 30000             | 26000              | 16000              |
| 最小工作质量    | Min. operating mass             | kg     | 20000             | 16000              | 10000              |
| 最高前进速度    | Max. travel speed               | km/h   | 20.5              | 20.5               | 14                 |
| 轮胎数量      | Tire number                     |        | 5+6               | 5+6                | 4+5                |
| 平均接地比压    | Tire contact pressure           | kPa    | 307 ~ 460         | 250 ~ 420          | 150 ~ 300          |
| 最小转弯半径    | Turning radius                  | mm     | 8400              | 8300               | 7500               |
| 碾压宽度      | Rolling width                   | mm     | 2790              | 2790               | 2290               |
| 轮胎重叠宽度    | Wheel overlap                   | mm     | 40                | 40                 | 40                 |
| 爬坡能力      | Gradeability                    | %      | 20                | 20                 | 20                 |
| 柴油机型号     | Diesel model                    |        | Cummins6BTA5.9    | Cummins6BT5.9      | Cummins4BT3.9      |
| 柴油机功率     | Diesel power                    | kW     | 125               | 110                | 75                 |
| 柴油机转速     | Diesel speed                    | r/min. | 2300              | 2300               | 2400               |
| 外形尺寸（驾驶室） | Overall dimensions(with cabin)  | mm     | 874 × 2790 × 3103 | 4874 × 2790 × 3100 | 4770 × 2290 × 3100 |
| 外形尺寸（遮阳蓬） | Overall dimensions(with canopy) | mm     |                   |                    | 4770 × 2290 × 3192 |

因产品在不断改进，规格、说明及外观如有变动，恕不另行通知，请谅。  
Since the product is improved continuously. The specification and instruction are subject to change without separate notice.